QINGDAO QUANHANG MACHINERY CO., LTD

Mortar Sprayer

Product Overview

The HB-4Q sprayer is a high-efficiency spraying device designed specifically for interior renovation and small-scale construction projects. It features a compact body, a built-in air compressor, and an automatic lubrication system, allowing it to easily pass through standard doorways to enter rooms for operation. It can complete construction tasks such as spraying wall mortar and paint without the need for an external air source; Its core advantages lie in its ultra-compact design, which allows the unit to maneuver flexibly in and out of various indoor spaces; the built-in air compressor eliminates the need for external equipment, saving on electricity costs while providing a stable air supply; and the automatic lubrication system effectively extends the service life of bearings, joints, and the feed piston. With three control modes (panel, remote, and pneumatic) flexibly adapt to different working conditions. Additionally, the push piston can be used continuously for over 100,000 square meters before replacement is needed, resulting in extremely low maintenance costs. It is the ideal choice for mechanized construction in residential renovations, small-scale repairs, and indoor spraying projects.



Technical Specifications

Maximum Theoretical Throughput	4 m^3/h
Maximum Pumping Pressure	2.5 MPa
Maximum Horizontal Conveying Distance	90m
Maximum Vertical Conveying Distance	28m
Feeding Pump	Twin-Cylinder Gravity Ball Valve Piston Pump
Concrete Drum Diameter/Stroke	Φ95/90mm
Maximum Particle Size	6mm
Hopper Capacity	0.28 m^3
Motor Power	5.5 kW
Feeding Height	900mm
Air Compressor Displacement	200L/min
Air Compressor Pressure	0.5 MPa
Dimensions	1700*850*1060mm
Weight	450 kg
Control Method	Control via the control panel, wireless control, pneumatic control

Qingdao Quanhang Machinery Co., Ltd

Key Benefits and Features of the Product

Compact design, making it easy to move in and out of rooms

The machine is small and compact, allowing it to easily pass through standard doorways to enter indoor work areas without the need to remove doors or move obstacles. Whether in the narrow rooms of a residential renovation project or during elevator transport in high-rise buildings, it can be flexibly deployed to the desired location, truly delivering the convenient construction experience of “the machine following the workers.”

Ultra-low maintenance costs—piston replacement required only every 100,000 square meters

The core pusher piston is made of high-strength, wear-resistant material and can be used continuously for over 100,000 square meters under normal operating conditions before replacement is required, significantly reducing the frequency of

consumable replacements. The overall maintenance cost is only one-third that of comparable products, resulting in significant long-term cost savings.

Stable operation, fast spraying

The equipment has undergone rigorous reliability testing, and its key components are manufactured using high-precision machining processes to ensure stable operation even during prolonged continuous use. With its fast spraying speed and uniform output, it can achieve a daily construction efficiency 4 to 6 times that of traditional manual methods, effectively shortening the construction schedule.

Built-in air compressor, saves electricity and ensures stable operation

The unit comes equipped with a high-quality air compressor, eliminating the need for an external air source and saving on the cost of purchasing an air compressor as well as the electricity consumption associated with a separate power supply. The built-in air compressor delivers a stable air flow, ensuring consistent spray atomization results, while the unit's lower power consumption results in significant savings on electricity bills over the long term.

Automatic lubrication system, extending the service life of the entire machine

Equipped with a fully automatic intelligent lubrication system, the machine supplies lubricant at regular intervals and in precise quantities to key moving parts—such as bearings, joints, and the push piston—during operation. This effectively reduces mechanical wear, significantly extends the service life of all transmission components and the push piston, and lowers the risk of unexpected downtime.

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

Three control modes for flexible adaptation to operating conditions

Supports three control modes—control panel, remote control, and pneumatic control—to meet the needs of various construction scenarios:

Control panel: Suitable for precise adjustments at close range; operation is intuitive.

Remote control: Operators can control the equipment from a distance, staying away from the spraying area to reduce dust exposure.

Pneumatic control: Compatible with automated production lines or integrated construction systems to enable linked control.

Applications

Chemical Industry: Pigments, coatings, plastic pellets, and premixed additives

Building Materials Industry: Dry-mixed mortar, joint compound, and insulation materials

Food Industry: Seasonings, milk powder, and protein powder blending

Pharmaceutical Industry: Pharmaceutical powders and raw material blending for nutritional supplements

Feed Industry: Production of premixes and concentrated feed

Why Choose Us?

Expert Technical Team: Over 10 years of experience in R&D of mixing equipment, providing customized solutions

Quality Assurance: Rigorous quality control system; ISO 9001-certified company

After-Sales Service: Global service network, 24-hour response, and lifetime technical support

Success Stories: Serving over 500 companies across more than 20 countries and regions

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

Customer Testimonial

1.

★★★★★ Project Manager, a major contracting company (Saudi Arabia)

The small concrete pump delivered flawless performance on our four-story building project — powerful, reliable, and easy to maneuver. It kept our schedule tight and the concrete placement precise. Highly recommend this machine for mid-rise construction.

2.

★★★★★ Construction Crew Foreman, a construction contracting company (Philippines)

This mortar spraying machine offers real advantages in both time and cost savings. It runs on electricity, so we’ ve saved significantly on expensive diesel fuel. We

completed the plastering of a 1,500 sq.ft flat in just 1.5 days — that would have taken us nearly a week with traditional methods.

3.

★★★★★ Engineer at a construction company, a certain construction firm (Malaysia)

The electric startup takes just minutes, and the remote-controlled valve adjustment makes operation effortless. We all love its smooth pumping operation — it's been a game-changer for our tunnel project.

FAQ

1.

Q: What is the minimum order quantity for your products?

A: For larger equipment such as mixers, our minimum order quantity is one unit; for smaller products such as valves and fittings, the minimum order quantity ranges from 50 to 100 pieces. Please contact our sales representatives to confirm the specific minimum order quantity.

2.

Q: From which port do you ship?

A: Since our company is located in Qingdao, most of our shipments depart from the Port of Qingdao.

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

3.

Q: Are you a factory or a trading company?

A: We are a manufacturing company with our own factory; all our equipment is produced in our factory's production lines.

4.

Q: How much greater is the efficiency of a mortar spray machine compared to manual application?

A: The construction efficiency of mechanical spraying is typically 3 to 8 times that of manual troweling. Taking a 100-square-meter wall as an example, manual troweling requires 2 to 3 people working an entire day, whereas using a mortar sprayer requires only 1 to 2 people and takes 2 to 4 hours to complete. Specific efficiency

depends on the mortar material, the condition of the wall substrate, and the operator's skill level.

5.

Q: What is the maximum area a mortar spray machine can cover in a day?

A: Taking a common fully automatic model as an example (such as the N5S model, with a delivery capacity of 20–30 L/min), under standard construction conditions, it can complete an average of 300–800 ㎡ of wall spraying per day. The actual area covered depends on factors such as the spray thickness (typically 5–20 mm), the type of mortar, and the construction environment.

6.

Q: What types of mortar materials can a mortar sprayer apply?

A: Mainstream mortar sprayers have a wide range of applications and can apply:

① Gypsum-based mortar (plastering and leveling)

② Cement-based mortar (plastering, masonry)

③ Lime-based mortar (traditional plastering)

④ Self-leveling mortar (floor leveling)

⑤ Insulation mortar (external wall insulation systems)

⑥ Repair mortar (crack filling, spot repairs)

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

7.

Q: What is the hopper capacity of a mortar spray machine? What is its purpose?

A: Hopper capacity is an important parameter for measuring a machine's continuous operation capability. Common models have hopper capacities ranging from 50L to 150L; the N5S model has a hopper capacity of 100L. The larger the hopper capacity, the less frequently the machine needs to be refilled, and the longer it can operate continuously; however, the overall weight and size of the machine will also increase accordingly.

8.

Q: What is the operating pressure (pumping pressure) of a mortar sprayer?

A: The N5S mortar sprayer has a delivery pressure of 30 bar, enabling it to reliably spray gypsum-based, cement-based, and self-leveling materials. Too low a pressure can result in uneven spraying and increased material rebound; too high a pressure

accelerates equipment wear. For high-rise construction projects, be mindful of pressure loss during vertical delivery and adjust the mix ratio accordingly.

9.

Q: Do I need professional training to operate the machine after receiving it?

A: Mortar sprayers are relatively easy to operate; you can get the hang of it after 0.5 to 1 day of hands-on training. Fully automatic models are even more user-friendly, as the machine handles most of the process automatically; operators are primarily responsible for loading materials, monitoring the spraying process, and performing simple maintenance. We recommend that the first group of operators receive on-site training at the manufacturer's facility or request remote video guidance from the manufacturer.

10.

Q: Is a mortar spray machine difficult to operate? Can one person operate it?

A: Fully automatic models have a low learning curve; a single skilled operator can complete spraying tasks independently. We recommend having one assistant responsible for continuous material feeding, as this can significantly improve continuous construction efficiency. For beginners, we suggest that two people work together for the first few jobs; once they become proficient, a single operator can independently complete standard operations.

11.

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

Q: What is the typical spray thickness for a mortar sprayer?

A: Wall plastering: The recommended thickness for a single application is 5–20 mm; if the thickness exceeds 20 mm, it is recommended to apply the material in two separate applications.

Self-leveling floors: The typical spray thickness is 3–15 mm, depending on the floor's levelness.

Repair and leveling: Localized thicknesses can reach 30–50 mm; in such cases, a thickening agent should be added or the application should be done in multiple passes.

Applying the mixture too thickly can cause sagging and cracking, while applying it too thinly results in insufficient coverage.

12.

Q: What should I do if the mortar spray machine clogs during operation?

A: Steps to resolve the issue:

Immediately shut down the machine and turn off the air supply;

Disassemble the clogged section and flush it with clean water or clear the blockage;

Check the mortar mix ratio (to see if it is too thick or contains foreign objects);

Readjust the water-to-cement ratio and resume operation.

Preventive Measures: Sift the mortar materials before use, control the consistency, and pump clean water through the pipes to moisten them before starting the machine.

13.

Q: How should a mortar spray machine be cleaned and maintained after a job is completed?

A: Cleaning is a key step in extending the equipment's service life:

① Immediate cleaning: Perform this within 30 minutes after the job is completed. After shutting down the machine, fill the hopper with clean water and run it to flush the system;

② Pump clean water: Pump a large volume of clean water through the pipes to flush out the pump chamber and piping;

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

③ Disassemble and clean the mixer: Remove the mixer assembly, rinse it with clean water, and wipe it dry;

④ Apply rust-preventive oil: Apply a thin layer of machine oil to metal contact surfaces to prevent rust;

⑤ Store in a dry place: Store the machine in a dry, well-ventilated area, away from direct exposure to rain.

14.

Q: Can a mortar sprayer be used for exterior wall construction?

A: Yes. Both exterior wall insulation mortar and plastering mortar can be applied using a sprayer. However, the following precautions should be taken for exterior wall construction:

Safety ropes and aerial work platforms must be used for work at heights.

Exterior wall spraying should be suspended when wind speeds are high (≥ Force 4) to prevent the mortar from being blown away.

Specialized nozzles and lower pumping pressure are typically used when spraying exterior wall insulation mortar.

15.

Q: What is the fundamental difference between a mortar sprayer and a concrete pump?

A: Although both involve pumping, they serve different functions:

Mortar sprayer: Sprays fine-aggregate mortar (aggregate ≤ 5 mm), emphasizing spray atomization and surface smoothness; primarily used for wall plastering and self-leveling floors

Concrete pump: Pumps coarse-aggregate concrete (aggregate up to 20 mm or larger), emphasizing high-pressure, long-distance delivery, and is used for structural construction.

The two cannot be used interchangeably; using the wrong material can cause serious damage to the equipment.

16.

青岛铨航机械设备有限公司
Qingdao Quanhang Machinery Co., Ltd

Q: Does the mortar spray machine come with a warranty? What does the warranty cover?

A: We offer a 1-year warranty on the entire machine. The main warranty coverage includes:

① Non-human-induced malfunctions of the motor, pump body, and control circuit board

② Issues such as seal failure or mortar leakage caused by product quality defects

The following are generally not covered by the warranty: wear-and-tear parts (mixer, O-rings, nozzles, stator, rotor), damage caused by human error, and normal wear and tear of consumable parts. We recommend purchasing 2–3 extra sets of consumable parts as spares when buying the machine.